

SUBMITTAL DATA SHEET
CH-12MSPHCT-230VI

Job Name:
 Location:
 Engineer:
 Submitted to:
 Submitted by:
 Reference:

Date:
 Approval:
 Construction:
 Unit #:
 Drawing #:


PERFORMANCE AND EFFICIENCY

Cooling		Heating	
12,000 Btu/h		12,000 Btu/h	
SEER	19.5	HSPF Region IV	10.6
EER	12.5		

OPERATION TEMPERATURE RANGE

cooling	heating
62~90°F	32~86°F

ELECTRICAL

Power supply	208-230V/ 60Hz, 1Ph
MCA	9 A
MFA	15 A
Fan motor	
Input	45 W
RLA	1 A

MCA: Minimum Circuit Ampacity **MFA:** Max. fuse A **RLA:** Rated load A

PIPING

Refrigerant piping Liquid/Gas side	1/4 - 1/2 in
------------------------------------	--------------



This warranty should be registered on our web-site www.cooperandhunter.us within 60 days of installation. The warranty is only valid when installed by a Licensed HVAC Technician. A warranty period of Seven (7) years on compressor to the original registered end-user. A warranty period of Five (5) years on all parts to the original registered end user. Warranty applies only to products remaining in their original installation location.

GENERAL FEATURES

- Activated Carbon Filter
- Mute Operation
- Sleep Mode
- 12 Grades Indoor Fan Speeds
- Self Diagnosis Function
- Two-way Draining Connection
- Golden fin for outdoor and indoor
- Two Direction Airflow
- Double Level Air Flaps
- High Density Filter
- Turbo Operation
- Refrigerant Leakage Detect
- Emergency Using Function

INDOOR SPECIFICATION

Air Flow (Hi/Mi/Lo)	338/288/248 CFM
Noise Level (Hi/Mi/Lo)	41/38/35 dB(A)
Unit Dimension(WxDxH)	22.44x22.44x10.24 in
Net/Gross Weight	35.27/41.88 lb

SUBMITTAL DATA SHEET

CH-12MSPHCT-230VI

