

SUBMITTAL DATA SHEET

CH-24MSPHCT-230VI

Job Name:
 Location:
 Engineer:
 Submitted to:
 Submitted by:
 Reference:

Date:
 Approval:
 Construction:
 Unit #:
 Drawing #:



PERFORMANCE AND EFFICIENCY

Cooling		Heating	
24,000 Btu/h		24,000 Btu/h	
SEER	20	HSPF	11.5
EER	11		

OPERATION TEMPERATURE RANGE

Cooling	Heating
62~90°F	32~86°F

ELECTRICAL

Power supply	208-230V/ 60Hz, 1Ph
MCA	20 A
MFA	30 A
Fan motor	
Input	58 W
RLA	2 A

MCA: Minimum Circuit Ampacity **MFA:** Max. fuse A **RLA:** Rated load A

PIPING

Refrigerant piping Liquid side/Gas side	3/8 - 5/8 in
---	--------------



This warranty should be registered on our web-site www.cooperandhunter.us within 60 days of installation. The warranty is only valid when installed by a Licensed HVAC Technician. A warranty period of Seven (7) years on compressor to the original registered end-user. A warranty period of Five (5) years on all parts to the original registered end user. Warranty applies only to products remaining in their original installation location.

GENERAL FEATURES

- Activated Carbon Filter
- Mute Operation
- Sleep Mode
- 12 Grades Indoor Fan Speeds
- Self Diagnosis Function
- Two-way Draining Connection
- Golden fin for outdoor and indoor
- Two Direction Airflow
- Double Level Air Flaps
- High Density Filter
- Turbo Operation
- Refrigerant Leakage Detect
- Emergency Using Function

INDOOR SPECIFICATION

Air Flow (Hi/Mi/Lo)	820/740/590 CFM
Noise Level (Hi/Mi/Lo)	51/47/43 dB(A)
Unit Dimension (W*D*H)	33.07x33.07x8.07 in
Net/Gross weight	45.19/52.91 lb

SUBMITTAL DATA SHEET

CH-24MSPHCT-230VI

