

SOPHIA Series

CASSETTE TYPE

SUBMITTAL DATA SHEET	CH-24MSPHCT-230VI		CH-HYP24SPH230V0	
Job Name:		Date:		
Lacation:		Approval:		
Engineer:		Construction:		
Submitted to:		Unit #:		
Submitted by:		Drawing #:		
Reference:				



VEAR COMPRESSOR VEAR PARTS

This warranty should be registered on our web-site www.cooperandhunter.us within 60 days of installation. The warranty is only valid when installed by a Licensed HVAC Technician. A warranty period of Seven (7) years on compressor to the original registered end-user. A warranty period of Five (5) years on all parts to the original registered end user. Warranty applies only to products remaining in their original installation location.

INDOOR SPECIFICATION

Air Flow (Hi/Mi/Lo)	820/740/590 CFM
Noise Level (Hi/Mi/Lo)	51/47/43 dB(A)
Unit Dimension (WxDxH)	33.07x33.07x8.07 in
Net/Gross weight	45.19/52.91 lb

OUTDOOR SPECIFICATION

Air flow	2354 CFM
Noise Level	60 dB(A)
Dimension (WxDxH)	37.24x16.14x31.89 in
Net/Gross weight	135.58/148.81 lb
Refrigerant type/Quantity	R410A/91.7 oz
Refrigerant precharge	25 ft
Additional charge for each ft	0.32 oz

PERFORMANCE AND EFFICIENCY

Cooling		Heating	
24,000 Btu/h		24,000 Btu/h	
SEER	20	HCDE	11.5
EER	11	HSPF	

OPERATION TEMPERATURE RANGE

Indoor		Outdoor	
cooling	heating	cooling	heating
62~90°F	32~86°F	-22~122°F	-22~86°F

ELECTRICAL

Power supply	208-230V/ 60Hz, 1Ph	
MCA	20 A	
MFA	30 A	

MCA: Minimum Circuit Ampacity

MFA: Max. fuse A

PIPING

Refrigerant piping Liquid side/Gas side	3/8 - 5/8 in
Max. refrigerant pipe length	164 ft
Max. difference in level	82 ft





SOPHIA Series

CASSETTE TYPE


SUBMITTAL DATA SHEET	CH-24MSPHCT-230VI	CH-HYP24SPH230V0
----------------------	-------------------	------------------


INDOOR UNIT





OUTDOOR UNIT





Outdoor Unit Dimensions	Mounting Dimensions	
WxDxH	Distance A	Distance B
37.24x16.14x31.89	26.5	15.87