

SUBMITTAL DATA SHEET
CH-M18DTUI

Job Name:
 Location:
 Engineer:
 Submitted to:
 Submitted by:
 Reference:

Date:
 Approval:
 Construction:
 Unit #:
 Drawing #:


PERFORMANCE AND EFFICIENCY

Cooling		Heating	
18,000 Btu/h		18,000 Btu/h	
SEER	19.0	COP	3.14
EER	12.5	HSPF4/ HSPF5	10.5/9

OPERATION TEMPERATURE RANGE

Cooling	Heating
62~90°F	32~86°F

ELECTRICAL

Power supply	208-230V/ 60Hz, 1Ph
MCA	15
MFA	20
Fan motor	
Input	90 W
RLA	1.2 A

MCA: Minimum Circuit Ampacity **MFA:** Max. fuse A **RLA:** Rated Load

PIPING

Refrigerant piping Liquid side/Gas side	1/4 - 1/2 in
---	--------------



This warranty should be registered on our web-site www.cooperandhunter.us within 60 days of installation. The warranty is only valid when installed by a Licensed HVAC Technician. A warranty period of Seven (7) years on compressor to the original registered end-user. A warranty period of Five (5) years on all parts to the original registered end user. Warranty applies only to products remaining in their original installation location.

FUTURES


- Flexible Installation
- Fresh Air Function
- Wired Control
- Multi-Channel Air Distribution
- Built-In Water Pump
- Golden fin for outdoor and indoor
- Lower Noise
- Higher Pipe Limits
- Slim Design

UNIT SPECIFICATION

Air Flow (Hi/Mi/Lo)	530/450/371 CFM
Noise Level (Hi/Mi/Lo)	39/37/35 dB(A)
Unit Dimension (W*D*H)	34.65x26.54x8.27 in
Net/Gross Weight	52.47/65.04 lb

SUBMITTAL DATA SHEET

CH-M18DTUI



Outline dimension				air outlet opening size		air return opening size		Size of mounted lug	
A	B	C	D	E	F	G	H	I	J
34.65	8.27	26.54	23.6	5.4	27.8	7.5	30.8	36.2	20